

516RT HIGH PERFORMANCE TROMMEL

The highly mobile McCloskey 516RT's high performance and customer-focused features have set the newest tracked trommel screener apart from the rest.

Boasting a heavy-duty chassis, four independent stabilizer jack legs, integrated folding hydraulic conveyors, and a radial fines conveyor with a 180° swing at a stockpiling height of 13' 6" (4.13m), the 516RT is built to get the job done. The 5' diameter, 16' long screen is ideal for a number of applications including topsoil, compost, sand, gravel, and wood.

The 516RT is equipped with McCloskey trommel features like a roomy engine bay and ground-adjustable brushes. It also features fully enclosed fines conveyor flashing and full-length rubber belting, minimizing spillage and reducing blockages.



Brushes

Ground level adjustable brushes keep the screen clean and rotate away from drum for ease of drum change.



Radial Conveyor

Radial conveyor with 180° swing and variable discharge height for maximum stockpiling flexibility.



Hopper Capacity

Hopper capacity of 5.25m³ (7yd³) with a 6' wide feed for free flow of material and high volume capacity.



Flashing

Fully enclosed fines flashing and full-length rubber belting minimize spillage and reduce blockages.



Lifting Bars

Deep lifting bars on a drum provide aggressive screening action.

516RT

Engine: 100 hp (75 kw) Diesel
Transport Height: 11' 8" (3.56m)
Transport Length: 49' 8" (15.13m)
Transport Width: 8' 11" (2.72m)
Weight: 50,000 lbs (22,500 kg) estimated

516RT HIGH PERFORMANCE TROMMEL

www.mccloskeyinternational.com

McCloskey International reserves the right to make changes to the information and design of the machines on this brochure without reservation and notification to the users. Information at time of print considered accurate – McCloskey International assumes no liability resulting from errors or omissions in this document.