

C38R

RECIRCULATING CONE CRUSHER

The McCloskey C38R recirculating cone crusher combines the productivity of the 38" cone with the versatility of a full screening and recirculating system, allowing operators to produce a high quality crushed and screened final product with one machine.

The C38R distinguishes itself as an entry-level cone with full level features like an anti-spin system, load and material level monitoring, fully hydraulic push button CSS adjust and full hydraulic relief system. The 5x10 High Energy Screenbox allows greater control over the final product.



RECIRCULATING SYSTEM

Recirculation conveyor allows operators to produce a crushed and screened final product with one machine.



RECIRCULATION SCREEN

5 X 10 High Energy Screenbox has a user-friendly wedge system for faster screen change

CRUSHING CHAMBER

Built to be reliable in the toughest operating conditions, the cone on the C38 produces 3/8" to 2" product.




FEEDER

Heavy Duty Hardox® steel hopper with adjustable feed rate via control panel, remote control or fully automatic regulation with feedback from the cone

METAL DETECTOR

A standard feature, the metal detector automatically stops the feeder when metal is detected as a way to prevent damage to the cone.



Engine	350 hp (261 kW) Diesel
Transport Height	11' 2" (3.40m)
Transport Length	56' 8.7" (17.29m)
Transport Width	10' 1" (3.08m)
Weight	100,300 lb (45,495kg)
Stockpile Height - Main Conveyor	9' 9" (2965mm)